



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

SC-200

Product Number: 2200

Product Division:

Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**

Medical Emergency: **1-(888)-314-6171 (24 hours)**

Chemical Leak/Spil Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Corrosive liquids, n.o.s., 8, UN 1760, II, (contains sodium hydroxide)

NFPA Ratings:	HMIS Ratings:
Health: 3 - Serious Fire: 0 - Minimal Reactivity: 0 - Minimal	Health: *3 - Serious; Chronic Hazard Fire: 0 - Minimal Reactivity: 0 - Minimal Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
*2-Butoxyethanol	5-10	111-76-2	240 [skin] 96	Not Established	Not Established	No
Alcohol ethoxylate	1-5	68439-46-3	Not Established	Not Established	Not Established	No
Sodium xylene sulfonate	1-5	1300-72-7	Not Established	Not Established	Not Established	No
Sodium hydroxide	1-5	1310-73-2	2	Not Established	Not Established	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: 210 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 13.4 - 13.9	Specific Gravity (H ₂ O=1): 1.063
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 14-15
Physical State: Liquid	
Appearance & Odor: Red liquid, glycol ether odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 210°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not support combustion. Use extinguishing media appropriate for surrounding fire.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.	
Unusual Fire & Explosive Hazards: Combustion products are toxic.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value: Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes & Oral
Effects of Overexposure- Conditions to Avoid:	CORROSIVE: CAUSES EYE AND SKIN BURNS: Symptoms include chemical burns, pain, redness, swelling of the conjunctiva and tissue destruction. HARMFUL CONTACT MAY NOT CAUSE IMMEDIATE PAIN HARMFUL IF SWALLOWED: Causes damage or chemical burns to esophagus and mucous membranes with symptoms of pain, nausea, vomiting and diarrhea. Aspiration of product into the lungs may occur during ingestion or vomiting, resulting in lung injury. HARMFUL IF INHALED: Breathing product vapor or mist may cause irritation or damage of the respiratory tract, with symptoms of nasal discomfort and discharge with chest pain and coughing. HARMFUL IF ABSORBED THROUGH SKIN: Contains 2-butoxyethanol which may cause central nervous system depression with symptoms such as headache; dizziness; nausea and drowsiness. Exposure to 2-butoxyethanol may cause blood cell; liver and kidney damage based on animal data. DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT BREATHE PRODUCT VAPOR OR MIST. DO NOT SWALLOW. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.
Conditions Aggravated by Use:	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis.

Emergency & First Aid Procedures:

Eyes:	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Remove contaminated clothing and shoes. Flush skin with water for at least 15 minutes. Get medical attention if irritation persists. Wash contaminated clothing before reuse. Destroy contaminated shoes.
Ingestion:	Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting. Drink one or two glasses of water to dilute product. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation or dizziness; move person to fresh air. If not breathing; give artificial respiration. If breathing is difficult; give oxygen. Get medical attention if irritation persists.

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong acids and oxidizing agents
Hazardous Decomposition Products: Not established	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Dike and contain spill with inert material (sand, earth, commercial absorbent, etc.) and transfer to containers for disposal. Rinse area with water and flush to sanitary sewer. Keep spill out of storm sewers and waterways.

Waste Disposal Method: Dispose of in compliance with all federal, state and local laws and regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not normally required when good general ventilation is provided. However if exposure limits are exceeded (see Section II) or if respiratory irritation occurs, the use of a NIOSH approved respirator suitable for the use-conditions and chemicals listed in Section II should be considered. (N95 or greater with organic vapor cartridge recommended)
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Solvent/alkali resistant gloves such as neoprene, nitrile or natural rubber.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	Solvent /alkali resistant boots, apron and other protective equipment is recommended when foot / body contact is likely. Eye wash stations and washing facilities should be readily accessible in areas where product is handled. See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Keep container tightly closed. Store in a cool, dry area. Do not freeze. Do not store above 120°F. Do not mix with other chemicals.
Other Precautions:	Keep out of reach of children

© SCC 05/15/2007 Name: Ronald T. Cook Title: Manager, Regulatory Affairs
SC-200 Effective Date: 05/15/2007 Supercedes: 04/30/2007
Ref: 29 CFR 1910.1200 (OSHA) Changes: Update Section VIII

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.